

Motor					Motor					System colour	
	MIN	MAX	kg/m			MIN	MAX	kg/m			
Modelite 35 DCT 230 V AC	-	1000	12,5	35	Irismo 45 WireFree RTS Li-ion	-	1000	12,5	45		
Modelite 35 WT 230 V AC	-	1000	12,5	35	Glydea 35e WT / 35e DCT 230 V AC	-	1000	12,5	35		
Modelite 35 RTS 230 V AC	-	1000	12,5	35	Glydea 60e WT / 60e DCT 230 V AC	-	1200	12,5	60		


The standard version includes a white Modelite/Iriso electric track with type A or B brackets and gliders (10 gliders per metre of track).

The end positions are not set in the standard version (follow the instructions supplied with the product).

The maximum system width without a track connector is 7 m. Manual operation is an option that allows the track to be opened/closed during a power failure. The 45 RTS motor is powered by a lithium-ion battery. The estimated number of operating cycles before the battery is discharged is 250

Slight colour differences between system components are permissible. Consultation is required before ordering / connecting to a smart home system.

Track



Glider



Brackets



ceiling



Adjustable bracket support

Battery




Irismo 45 RTS



Irismo 45 RTS

Modelite 35 RTS

Microflex



Touch Motion



Special extended gliders allow Microflex fabric holders to be used, which make the fabric height adjustable.

The option is not available with a profile connector.

It only starts the movement. The track cannot be stopped with this function.



Glydea Ultra

UP



With suspended ceilings the motor can be fitted on top and so concealed.

Fabric pleats



Special gliders and a tape sewn into the fabric form the fabric pleats.

tandem Modelite 35 DCT/WT

tandem Modelite 35 RTS

tandem Irismo 45 RTS

Movelite / Irismo load capacity table

	Track type	Load capacity (fabric weight)* [kg]									
		1m	2m	3m	4m	5m	6m	7m	8m	9m	10m
45 RTS	straight track	13	25	38	45						
35 DCT 35 WT 35 RTS	straight track	13	25	35							
	1 curve 2	13	25	35	25			20			
	curves	13	15		10		x	x	x	x	x
	bay window curve	13	25	30	10	x	x	x	x	x	x
45 RTS Tandem	straight track	13	25	38	50	63	75	88	90		
35 DCT Tandem 35 WT Tandem 35 RTS Tandem	straight track	13	25	45	60						
	1 curve 2	13	25	45							
	curves	13	25	35			25				
	bay window curve	13	30					25		x	x

* theoretical figures - max. glider load capacity 1.25 kg; with the Microflex option the permissible track load is 80% of the value in the table.

Glydea Ultra load capacity table

	Track type	Load capacity (fabric weight)* [kg]													
		1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m		
35e WT 35e DCT 35e RTS	straight track	13	25	35											
	1 curve 2	13	25	35	25			20				x	x		
	curves	13	15		10		x	x	x	x	x	x	x		
	bay window curve	13	25	10		x		x	x	x	x	x	x		
60e WT 60e DCT 60e RTS	straight track	13	25	38	50	60						55			
	1 curve 2	13	25	38	45					35					
	curves	13	25	35			25			x				x	x
	bay window curve	13	25	30			20		x	x	x	x	x		

* theoretical figures - max. glider load capacity 1.25 kg; with the Microflex option the permissible track load is 80% of the table value.



glider
ceiling bracket wall
bracket track connector
microflex 95 mm (pcs.)
microflex 95 mm (pcs.)
microflex 95 mm (pcs.)



motor fitted on top - UP curve with
a 30 cm / 45 cm radius bay window
curve
fabric pleat tape (clear) (m) - Snap fabric pleat tape
(m) - Wave
RJ12 cable

